

SSOUNDS A34X

Coming soon. 4-channel Class-D amplifier, 4 × 3,000 W at 8 Ω, analog input, no onboard DSP.

IMAGE ON REQUEST

AT A GLANCE

MODEL / SKU

SS-A34X

CATEGORY

Amplifiers

BRAND

SSOUNDS

POWER

24000 W

CONDITION

New

APPLICATIONS

AMPLIFIER

ANALOG

TOURING

INSTALL

OVERVIEW

The A34X is the analog counterpart to the D34X: the same four Class-D channels at 3,000 W each into 8 Ω, without the onboard DSP, Dante or network control. Specify it where processing already lives upstream in a system processor and all you need is the power. Contact us to register interest or to plan a system around it.

- Coming soon, shipping date on request
- 4 × 3,000 W into 8 Ω, 4 × 6,000 W into 4 Ω, 24,000 W total
- Same output stage as the D34X, without onboard DSP
- Analog XLR input with selectable sensitivity
- For systems processed upstream by an external DSP

TECHNOLOGIES



DYNACONTROL

Holds the tuned tonal balance as voice coils heat under sustained output.

SPECIFICATIONS

GENERAL

Type	4-channel Class-D power amplifier, analog input
Protection	Over-current · thermal · DC · short-circuit
Cooling	Forced-air front-to-rear, variable-speed fans under continuous temperature monitoring
Certifications	CE · UKCA · TÜV (rack mounting) · FCC · cULus · EAC · RoHS

PERFORMANCE

Frequency response	20 Hz - 20 kHz (±0.5 dB)
THD+N	< 0.05% @ 1 kHz
S/N ratio	> 112 dB (A-weighted)
Damping factor	> 400 @ 8 Ω

ELECTRICAL

Channels	4 × Class-D
Power @ 8 Ω	4 × 3,000 W
Power @ 4 Ω	4 × 6,000 W
Minimum load impedance ¹	2 Ω (all channels driven)
Bridged @ 8 Ω	2 × 12,000 W
Total output	24,000 W
Mains	200-240 V switch-mode with PFC

CONNECTORS & I/O

Inputs / outputs	4 × XLR in · 4 × NL4 speakON out
Input sensitivity	0 dBu / 6 dBu selectable

PHYSICAL & CONSTRUCTION

Format	19" 2U rack
Net weight ²	14 kg / 31 lb

ENVIRONMENT

Operating temperature	-10 °C to +40 °C continuous, +50 °C short term
Storage temperature	-20 °C to +70 °C
Humidity	< 70% relative humidity, non-condensing

NOTES

1. Nominal impedance is the manufacturer's rating for amplifier load calculation; minimum impedance across the operating band may be lower.
2. Net weight excludes packaging, flight case, accessories and optional rigging hardware.
3. All figures are typical values for production units specified under the conditions above. Individual units may vary within published tolerances.

DOWNLOADS & DATA FILES

SSOUNDS A34X: User Manual

MANUAL

Loudspeaker data files for prediction software (GLL / CLF for EASE), 2D and 3D drawings and certification documents are issued on request. Contact support@s-soundspro.com and we will send the current release for this model.

ARCHITECTURAL & ENGINEERING SPECIFICATION

The amplifier shall be of the SSOUNDS A34X type, configured as a 4-channel Class-D power amplifier, analog input. The amplifier shall be capable of meeting the following performance criteria: a frequency response of 20 Hz – 20 kHz (± 0.5 dB); a sensitivity of 0 dBu / 6 dBu selectable. Electrically the amplifier shall provide a power rating of 24000 W, a nominal impedance of 2 Ω (all channels driven). Connection shall be by 4 x XLR in, 4 x NL4 speakON out. The amplifier shall weigh 14 kg / 31 lb. The amplifier shall be covered by the manufacturer's two (2) year limited warranty and shall be supplied by SSOUNDS or an SSOUNDS-authorized distributor. No alternate shall be accepted without prior written approval of the consultant or specifying engineer.

SAFETY & COMPLIANCE

Read this section before specifying, installing or operating this product. It summarises the safety requirements set out in full in the product documentation supplied with the unit; where the two differ, the product documentation takes precedence.

SOUND PRESSURE LEVEL & HEARING

This equipment is capable of producing sound pressure levels that cause permanent hearing damage. Do not operate at high level in close proximity, and ensure that operators, performers and audience exposure complies with applicable occupational noise-exposure regulation. Provide hearing protection where exposure limits may be exceeded.

ELECTRICAL SAFETY

Connect only to a correctly earthed supply of the voltage and frequency stated on this sheet and on the product rating label. Where the supply is a generator, confirm stable voltage and frequency and adequate earthing before connection; unstable supply is the most common cause of amplifier failure and is not covered by warranty. Do not operate with a damaged mains lead or connector. There are no user-serviceable parts inside. Refer all servicing to SSOUNDS or an authorised service centre.

ENVIRONMENT & MECHANICAL

Unless a published IP rating states otherwise, this product is intended for indoor use or for outdoor use under cover, and must be protected from rain, standing water and prolonged direct sun. Ensure ventilation openings are unobstructed. Stack, pole-mount and transport only as described in the product documentation, and secure the product against toppling wherever the public has access.

DISPOSAL

At end of life, dispose of the product and any packaging in accordance with local regulation for electrical and electronic equipment. Do not dispose of electronic components in general waste.

LIMITED WARRANTY: TWO (2) YEARS

SSOUNDS products are warranted against defects in materials and workmanship for a period of two (2) years from the original date of purchase by the end user. Within that period SSOUNDS will, at its option, repair or replace the defective item with no charge for parts or labour. The item must be adequately packaged and dispatched, carriage pre-paid, to SSOUNDS or an SSOUNDS-authorised service centre, accompanied by proof of purchase and a returns reference issued in advance by SSOUNDS. Unauthorised repair, modification or removal of serial-number labelling voids this warranty.

THIS WARRANTY DOES NOT COVER

- Cosmetic wear, finish, grille cloth, paintwork and consumable parts.
- Damage caused by misuse, abuse, accident, neglect, or operation outside the published ratings on this sheet.
- Damage caused by transport or handling after delivery, or by inadequate packaging on return.
- Damage caused by mains or generator supply faults (over-voltage, under-voltage, phase imbalance, surge or incorrect earthing) or by lightning.
- Water, dust or corrosion ingress on products not carrying a published IP rating for the conditions of use.
- Damage resulting from amplification or processing outside the recommended configuration on this sheet, or from third-party presets.
- Products not purchased from SSOUNDS or an SSOUNDS-authorised distributor.

This warranty is in addition to, and does not affect, any statutory rights the purchaser may have under applicable consumer law. It is the sole warranty offered; no other warranty, express or implied, is given.

Warranty claims and returns references: support@s-soundspro.com · +44 20 3769 6537

LEGAL NOTICE

All information on this data sheet is subject to change without notice. SSOUNDS reserves the right to alter specification, design and construction in the course of continuous product development.

Specifications, drawings and images are provided for guidance in system design and tender documentation. Where a figure is critical to a design, confirm it in writing with SSOUNDS before committing to a specification.

All text, images and drawings herein are the property of SSOUNDS. All trademarks and registered trademarks are the property of their respective owners.

S SOUNDS PRO LTD
82a James Carter Road, Mildenhall, IP28 7DE, United Kingdom
+44 20 3769 6537 · support@s-soundspro.com

SSOUNDS · ...enhancing listening pleasure! · s-soundspro.com · support@s-soundspro.com
© 2026 S Sounds Pro Ltd. All rights reserved. Specifications subject to change without notice.

SS-DS-A34X-EN-A4 · Rev. 2608 · Issued 14 Aug 2026