

SSOUNDS M4.2P

Compact two-way cabinet, 2 × 4" in V formation with a compression driver, 100 dB sensitivity, 126 dB peak.

M stands for Modular.



SSOUNDS M4.2P

AT A GLANCE

MODEL / SKU	CATEGORY
SS-M42P	Point Source Speakers
BRAND	DRIVE
SSOUNDS	Passive
CONDITION	
New	
APPLICATIONS	
INSTALL	FILL
COMPACT	COMMERCIAL

OVERVIEW

The M4.2P is a compact two-way cabinet for fill and foreground duty where a small box has to keep up with a larger system. Two 4" long-excursion drivers in V formation sit beside a compression driver with a 0.5" throat and 1" voice coil, giving 100 dB sensitivity and 126 dB peak at 1 m from 95 Hz to 20 kHz. The name follows the M3 columns: driver size, then driver count. We specify it for front fill, under-balcony and delay positions, bars and foyers.

- 2 × 4" long-excursion LF in V formation
- Compression driver, 0.5" throat, 1" voice coil
- 95 Hz to 20 kHz (±6 dB)
- 100 dB sensitivity, 126 dB peak at 1 m
- 200 to 500 W recommended amplifier power
- 16 Ω nominal impedance

SPECIFICATIONS

GENERAL

Type	Passive 2-way compact loudspeaker
------	-----------------------------------

ACOUSTIC PERFORMANCE

Frequency response ²	95 Hz - 20 kHz (±6 dB)
Maximum SPL ¹	126 dB peak @ 1 m
Sensitivity ³	100 dB (1 W @ 1 m)

TRANSDUCERS & COMPONENTS

Low frequency	2 × 4" long-excursion drivers, V formation
High frequency	1 × compression driver, 0.5" throat, 1" voice coil

ELECTRICAL

Recommended amplifier power ⁴	200 - 500 W
Nominal impedance ⁵	16 Ω

NOTES

1. Maximum SPL is the peak level at 1 m, driven with pink noise at crest factor 4 to the clipping point of the recommended amplifier, with the SSOUNDS system preset applied. Full-range enclosures are specified under free-field conditions; figures marked half-space are specified over a reflecting plane, the condition subwoofers are deployed in, which adds approximately 6 dB.
2. Frequency response is specified on axis at 1 m in a free field. The tolerance the figure is referenced to is stated alongside it; where no tolerance is given, the figure is the -6 dB bandwidth.
3. Sensitivity is specified at 1 W into the nominal impedance at 1 m on axis, averaged across the pass band of the enclosure.
4. Recommended amplifier power is the amplifier output SSOUNDS specifies for this enclosure, driven with the SSOUNDS system preset. It guides amplifier selection and is not an AES power-handling rating for the transducers.
5. Nominal impedance is the manufacturer's rating for amplifier load calculation; minimum impedance across the operating band may be lower.
6. All figures are typical values for production units specified under the conditions above. Individual units may vary within published tolerances.

Directivity (isobars / balloon). Measured directivity data (isobars, balloon and GLL/CLF for EASE) is in preparation. We publish measured polars only. Contact us for the current measurement status of this model.

DOWNLOADS & DATA FILES

SSOUNDS M4.2P: User Manual

MANUAL

Loudspeaker data files for prediction software (GLL / CLF for EASE), 2D and 3D drawings and certification documents are issued on request. Contact support@s-soundspro.com and we will send the current release for this model.

ARCHITECTURAL & ENGINEERING SPECIFICATION

The loudspeaker shall be of the SSOUNDS M4.2P type, configured as a passive 2-way compact loudspeaker. The loudspeaker shall incorporate a low-frequency section of 2 × 4" long-excursion drivers, V formation, a high-frequency section of 1 × compression driver, 0.5" throat, 1" voice coil. The loudspeaker shall be capable of meeting the following performance criteria: a frequency response of 95 Hz – 20 kHz (±6 dB); a maximum sound pressure level of 126 dB peak @ 1 m; a sensitivity of 100 dB (1 W @ 1 m). Electrically the loudspeaker shall provide a nominal impedance of 16 Ω. The unit shall be passive. The loudspeaker shall be covered by the manufacturer's two (2) year limited warranty and shall be supplied by SSOUNDS or an SSOUNDS-authorized distributor. No alternate shall be accepted without prior written approval of the consultant or specifying engineer.

SAFETY & COMPLIANCE

Read this section before specifying, installing or operating this product. It summarises the safety requirements set out in full in the product documentation supplied with the unit; where the two differ, the product documentation takes precedence.

SUSPENSION & RIGGING

Overhead suspension is potentially hazardous and must be carried out only by trained and competent personnel using SSOUNDS-approved hardware, within the working load limits and array configurations published in the relevant SSOUNDS rigging documentation. Never exceed the stated number of enclosures per array or the stated splay limits. Inspect all rigging components, pins and retaining clips before every deployment and withdraw from service any component that is deformed, corroded or of unknown history. Secondary safety attachment is required where local regulation calls for it. SSOUNDS accepts no liability for systems suspended using non-approved hardware or outside published limits.

SOUND PRESSURE LEVEL & HEARING

This equipment is capable of producing sound pressure levels that cause permanent hearing damage. Do not operate at high level in close proximity, and ensure that operators, performers and audience exposure complies with applicable occupational noise-exposure regulation. Provide hearing protection where exposure limits may be exceeded.

ENVIRONMENT & MECHANICAL

Unless a published IP rating states otherwise, this product is intended for indoor use or for outdoor use under cover, and must be protected from rain, standing water and prolonged direct sun. Ensure ventilation openings are unobstructed. Stack, pole-mount and transport only as described in the product documentation, and secure the product against toppling wherever the public has access.

DISPOSAL

At end of life, dispose of the product and any packaging in accordance with local regulation for electrical and electronic equipment. Do not dispose of electronic components in general waste.

LIMITED WARRANTY: TWO (2) YEARS

SSOUNDS products are warranted against defects in materials and workmanship for a period of two (2) years from the original date of purchase by the end user. Within that period SSOUNDS will, at its option, repair or replace the defective item with no charge for parts or labour. The item must be adequately packaged and dispatched, carriage pre-paid, to SSOUNDS or an SSOUNDS-authorised service centre, accompanied by proof of purchase and a returns reference issued in advance by SSOUNDS. Unauthorised repair, modification or removal of serial-number labelling voids this warranty.

THIS WARRANTY DOES NOT COVER

- Cosmetic wear, finish, grille cloth, paintwork and consumable parts.
- Damage caused by misuse, abuse, accident, neglect, or operation outside the published ratings on this sheet.
- Damage caused by transport or handling after delivery, or by inadequate packaging on return.
- Damage caused by mains or generator supply faults (over-voltage, under-voltage, phase imbalance, surge or incorrect earthing) or by lightning.
- Water, dust or corrosion ingress on products not carrying a published IP rating for the conditions of use.
- Damage resulting from amplification or processing outside the recommended configuration on this sheet, or from third-party presets.
- Products not purchased from SSOUNDS or an SSOUNDS-authorised distributor.

This warranty is in addition to, and does not affect, any statutory rights the purchaser may have under applicable consumer law. It is the sole warranty offered; no other warranty, express or implied, is given.

Warranty claims and returns references: support@s-soundspro.com · +44 20 3769 6537

LEGAL NOTICE

All information on this data sheet is subject to change without notice. SSOUNDS reserves the right to alter specification, design and construction in the course of continuous product development.

Specifications, drawings and images are provided for guidance in system design and tender documentation. Where a figure is critical to a design, confirm it in writing with SSOUNDS before committing to a specification.

All text, images and drawings herein are the property of SSOUNDS. All trademarks and registered trademarks are the property of their respective owners.

S SOUNDS PRO LTD

82a James Carter Road, Mildenhall, IP28 7DE, United Kingdom
+44 20 3769 6537 · support@s-soundspro.com

SSOUNDS · ...enhancing listening pleasure! · s-soundspro.com · support@s-soundspro.com
© 2026 S Sounds Pro Ltd. All rights reserved. Specifications subject to change without notice.

SS-DS-M42P-EN-A4 · Rev. 2610 · Issued 08 Oct 2026