

SSOUNDS P10T

Three-way 10" install loudspeaker in an IP67 moulded ABS cabinet, 50 Hz to 20 kHz, on a 70/100 V line or at 8 Ω, for worship, hospitality, retail, courtyards and conference rooms.

P stands for Point Source.

AT A GLANCE

MODEL / SKU	CATEGORY
SS-P10T	Point Source Speakers
BRAND	DRIVE
SSOUNDS	Passive
POWER	CONDITION
300 W	New
APPLICATIONS	
INSTALLCOMMERCIALSPEECHFILL	



SSOUNDS P10T - PRODUCT VIEWS

OVERVIEW

Restaurants, shops, meeting rooms, courtyards and the side areas of a prayer hall need a loudspeaker that sounds full with music, stays clear with speech, and sits on a wall indoors or out without looking like stage equipment. The P10T is a commercial-install point source in the same 10" format as our wooden M-10: a passive three-way cabinet with a 10" low-frequency driver, a 5" mid and a 1" high-frequency driver in a moulded ABS enclosure rated IP67, with a spray finish and a powder-coated steel grille, in black or white. It reaches 50 Hz, covers 90° by 60°, and mounts on a wall bracket. It runs either on a 70/100 V distributed line or at 8 Ω from an amplifier channel, and the connector is chosen at order, screw-terminal plug-in, NL4 speakON or banana binding posts, so it lands on whatever cable the installer is already running. We specify it for houses of worship, mosques and their courtyards, restaurants, retail, conference rooms, covered outdoor areas and background or foreground music.

- Three-way: 1 × 10" LF, 1 × 5" mid, 1 × 1" HF
- 50 Hz to 20 kHz (–10 dB)
- 90° × 60° coverage
- 99 dB sensitivity, 129 dB peak at 1 m
- 300 W power handling, 600 W recommended amplifier
- 70/100 V line or 8 Ω low-Z
- IP67 moulded ABS cabinet, black or white, wall bracket, 8.6 kg
- Connector specified at order: screw terminal, NL4 speakON or binding posts

SPECIFICATIONS

GENERAL

Type	Passive 3-way full-range, ABS install cabinet
------	---

ACOUSTIC PERFORMANCE

Frequency response ²	50 Hz – 20 kHz (–10 dB)
Coverage ⁴	90° × 60°
Maximum SPL ¹	129 dB peak @ 1 m
Sensitivity ³	99 dB (1 W @ 1 m)

TRANSDUCERS & COMPONENTS

Low frequency	1 × 10" driver
Mid frequency	1 × 5" driver
High frequency	1 × 1" driver

ELECTRICAL

Amplification	Passive, one channel of a SSOUNDS D14X system DSP amplifier per cabinet (4 cabinets per amplifier)
Power handling ⁵	300 W
Recommended amplifier power ⁶	600 W
Nominal impedance ⁷	8 Ω
Operation	70 / 100 V line (tapped) or 8 Ω low-Z
Crossover	Passive 3-way

CONNECTORS & I/O

Connectors	Specified at order: screw-terminal plug-in, NL4 speakON or banana binding posts (in / link)
------------	--

RIGGING & MOUNTING

Mounting	Wall bracket
----------	--------------

PHYSICAL & CONSTRUCTION

Dimensions (H × W × D) ⁹	480 × 285 × 300 mm
Net weight ⁸	8.6 kg / 19 lb
Enclosure	ABS · spray finish · powder-coated steel grille
Colour	Black or white

ENVIRONMENT


Ingress protection	IP67
--------------------	------

NOTES

- 1. Maximum SPL is the peak level at 1 m, driven with pink noise at crest factor 4 to the clipping point of the recommended amplifier, with the SSOUNDS system preset applied. Full-range enclosures are specified under free-field conditions; figures marked half-space are specified over a reflecting plane, the condition subwoofers are deployed in, which adds approximately 6 dB.
- 2. Frequency response is specified on axis at 1 m in a free field. The tolerance the figure is referenced to is stated alongside it; where no tolerance is given, the figure is the -6 dB bandwidth.
- 3. Sensitivity is specified at 1 W into the nominal impedance at 1 m on axis, averaged across the pass band of the enclosure.
- 4. Coverage angles are nominal -6 dB values averaged across the pass band. Per-octave directivity data is available from SSOUNDS system design support for prediction and modelling.
- 5. Power handling is rated to AES2 using pink noise with a 6 dB crest factor over a two-hour period. Programme power is twice the AES rating; peak power is four times.
- 6. Recommended amplifier power is the amplifier output SSOUNDS specifies for this enclosure, driven with the SSOUNDS system preset. It guides amplifier selection and is not an AES power-handling rating for the transducers.
- 7. Nominal impedance is the manufacturer's rating for amplifier load calculation; minimum impedance across the operating band may be lower.
- 8. Net weight excludes packaging, flight case, accessories and optional rigging hardware.
- 9. Dimensions are stated in millimetres and exclude protruding rigging hardware, handles and connector panels unless noted.
- 10. All figures are typical values for production units specified under the conditions above. Individual units may vary within published tolerances.


RESPONSE

FREQUENCY RESPONSE



Frequency response: 50 Hz to 20 kHz (-10 dB) · 1/24-octave smoothed

HORIZONTAL BEAMWIDTH




-6 dB horizontal beamwidth: 90° nominal

Plot conditions. Curves are generated by the SSOUNDS engineering toolchain from this product's specification. Frequency response is shown 1/24-octave smoothed, normalised to the midband reference, with the passband corners at the stated tolerance; response varies within ± 1 dB across the passband with a subtle shelf in the top octave. Magnitude slopes are 24 dB/octave beyond the passband corners. The beamwidth curve shows the -6 dB included angle: nominal coverage holds down to the pattern-control limit set by the cabinet width ($f \approx c/w$) and widens below it.


DIRECTIVITY

ISOBAR DIAGRAM, HORIZONTAL




Lines of equal sound pressure. Blue: -6 dB. Dashed: -12 dB. White region holds within 6 dB of on-axis.

ISOBAR DIAGRAM, VERTICAL




Lines of equal sound pressure. Blue: -6 dB. Dashed: -12 dB. White region holds within 6 dB of on-axis.

POLAR RESPONSE, HORIZONTAL



Normalised to on-axis. Rings at 6 dB intervals to a -30 dB centre. 1/3-octave band power. Charts span 50 Hz to 16 kHz, this cabinet's own operating band.

POLAR RESPONSE, VERTICAL



Normalised to on-axis. Rings at 6 dB intervals to a -30 dB centre. 1/3-octave band power.

Chart conditions. Directivity charts are computed by the SSOUNDS system prediction engine as a phase-coherent wave solution of this product's driver complement: each way represented by its physical radiator (rigid-piston cones with real diameters and spacings; waveguides as continuous mouth apertures, holding the rated coverage on a flare-controlled axis above the mouth's pattern-control limit and radiating the mouth's own diffraction limit on a wavefront-shaped axis; a horn-loaded mid shares the high-frequency mouth), summed as complex pressure through crossovers at the published points in the topology the cabinet is driven with (linear-phase FIR where the ways run on separate channels of a system DSP amplifier, Linkwitz-Riley where a passive network splits them), with way alignment referenced on axis and 1/24-octave band-power resolution. Single-cabinet vertical figures are free-field beamwidths of one element; the published per-element vertical coverage of a line array is its rigging splay, the sector one element covers in a curved hang. Cabinet edge diffraction, horn loading detail, driver breakup and production tolerances are outside the computation. Directivity files for prediction software (GLL/CLF) are issued from measured data only.

DOWNLOADS & DATA FILES

SSOUNDS P10T: User Manual	MANUAL
Directivity table, horizontal (CSV) / vertical	CSV
SSOUNDS M-10i: Technical Data Sheet	DATASHEET

Loudspeaker data files for prediction software (GLL / CLF for EASE), 2D and 3D drawings and certification documents are issued on request. Contact support@s-soundspro.com and we will send the current release for this model.

ARCHITECTURAL & ENGINEERING SPECIFICATION

The processor shall be of the SSOUNDS P10T type, configured as a passive 3-way full-range, ABS install cabinet. The processor shall incorporate a low-frequency section of 1 × 10" driver, a mid-frequency section of 1 × 5" driver, a high-frequency section of 1 × 1" driver. The processor shall be capable of meeting the following performance criteria: a frequency response of 50 Hz – 20 kHz (–10 dB); a maximum sound pressure level of 129 dB peak @ 1 m; a sensitivity of 99 dB (1 W @ 1 m); nominal coverage of 90° × 60°. Electrically the processor shall provide a power handling of 300 W, a nominal impedance of 8 Ω, a crossover at Passive 3-way. Connection shall be by Specified at order: screw-terminal plug-in, NL4 speakON or banana binding posts (in / link). The processor shall be constructed of ABS, spray finish, powder-coated steel grille, measuring 480 × 285 × 300 mm, and shall weigh 8.6 kg / 19 lb. Rigging provision shall be Wall bracket. The processor shall be covered by the manufacturer's two (2) year limited warranty and shall be supplied by SSOUNDS or an SSOUNDS-authorized distributor. No alternate shall be accepted without prior written approval of the consultant or specifying engineer.

SAFETY & COMPLIANCE

Read this section before specifying, installing or operating this product. It summarises the safety requirements set out in full in the product documentation supplied with the unit; where the two differ, the product documentation takes precedence.

SUSPENSION & RIGGING

Overhead suspension is potentially hazardous and must be carried out only by trained and competent personnel using SSOUNDS-approved hardware, within the working load limits and array configurations published in the relevant SSOUNDS rigging documentation. Never exceed the stated number of enclosures per array or the stated splay limits. Inspect all rigging components, pins and retaining clips before every deployment and withdraw from service any component that is deformed, corroded or of unknown history. Secondary safety attachment is required where local regulation calls for it. SSOUNDS accepts no liability for systems suspended using non-approved hardware or outside published limits.

SOUND PRESSURE LEVEL & HEARING

This equipment is capable of producing sound pressure levels that cause permanent hearing damage. Do not operate at high level in close proximity, and ensure that operators, performers and audience exposure complies with applicable occupational noise-exposure regulation. Provide hearing protection where exposure limits may be exceeded.

ENVIRONMENT & MECHANICAL

Unless a published IP rating states otherwise, this product is intended for indoor use or for outdoor use under cover, and must be protected from rain, standing water and prolonged direct sun. Ensure ventilation openings are unobstructed. Stack, pole-mount and transport only as described in the product documentation, and secure the product against toppling wherever the public has access.

DISPOSAL

At end of life, dispose of the product and any packaging in accordance with local regulation for electrical and electronic equipment. Do not dispose of electronic components in general waste.

LIMITED WARRANTY: TWO (2) YEARS

SSOUNDS products are warranted against defects in materials and workmanship for a period of two (2) years from the original date of purchase by the end user. Within that period SSOUNDS will, at its option, repair or replace the defective item with no charge for parts or labour. The item must be adequately packaged and dispatched, carriage pre-paid, to SSOUNDS or an SSOUNDS-authorised service centre, accompanied by proof of purchase and a returns reference issued in advance by SSOUNDS. Unauthorised repair, modification or removal of serial-number labelling voids this warranty.

THIS WARRANTY DOES NOT COVER

- Cosmetic wear, finish, grille cloth, paintwork and consumable parts.
- Damage caused by misuse, abuse, accident, neglect, or operation outside the published ratings on this sheet.
- Damage caused by transport or handling after delivery, or by inadequate packaging on return.
- Damage caused by mains or generator supply faults (over-voltage, under-voltage, phase imbalance, surge or incorrect earthing) or by lightning.
- Water, dust or corrosion ingress on products not carrying a published IP rating for the conditions of use.
- Damage resulting from amplification or processing outside the recommended configuration on this sheet, or from third-party presets.
- Products not purchased from SSOUNDS or an SSOUNDS-authorised distributor.

This warranty is in addition to, and does not affect, any statutory rights the purchaser may have under applicable consumer law. It is the sole warranty offered; no other warranty, express or implied, is given.

Warranty claims and returns references: support@s-soundspro.com · +44 20 3769 6537

LEGAL NOTICE

All information on this data sheet is subject to change without notice. SSOUNDS reserves the right to alter specification, design and construction in the course of continuous product development.

Specifications, drawings and images are provided for guidance in system design and tender documentation. Where a figure is critical to a design, confirm it in writing with SSOUNDS before committing to a specification.

All text, images and drawings herein are the property of SSOUNDS. All trademarks and registered trademarks are the property of their respective owners.

S SOUNDS PRO LTD
82a James Carter Road, Mildenhall, IP28 7DE, United Kingdom
+44 20 3769 6537 · support@s-soundspro.com

SSOUNDS · ...enhancing listening pleasure! · s-soundspro.com · support@s-soundspro.com
© 2026 S Sounds Pro Ltd. All rights reserved. Specifications subject to change without notice.

SS-DS-P10T-EN-A4 · Rev. 2610 · Issued 09 Oct 2026