


Unilumin Upad IV-S

Tight-curve creative rental LED, $\pm 40^\circ$ per panel, full circles from just 9 cabinets.



AT A GLANCE

MODEL / SKU	CATEGORY
UL-UPAD4S	LED / Video
BRAND	DRIVE
Unilumin	Passive
CONDITION	
New	

OVERVIEW

The Upad IV-S is the creative variant of the Upad IV: the same P2.6 rental platform with hinges that curve to $\pm 40^\circ$ per panel, a full 360° cylinder from only nine cabinets. Waves, totems, S-curves and shapes no flat panel can approximate, at 1,200 nits and up to 7,680 Hz.

SPECIFICATIONS

GENERAL

Type	Tight-curve creative rental LED
------	---------------------------------

DISPLAY

Pixel pitch	P2.6
Brightness	1,200 nits
Refresh rate	3,840 - 7,680 Hz @60

PANEL GEOMETRY

Curve ±40° per panel · full circle from 9 panels · waves + totems

PHYSICAL & CONSTRUCTION

Cabinet 500 × 500 × 80 mm · 7.7 kg

ENVIRONMENT

Rating IP4X

DOWNLOADS & DATA FILES

[Unilumin Upad IV-S: User Manual](#) MANUAL

Loudspeaker data files for prediction software (GLL / CLF for EASE), 2D and 3D drawings and certification documents are issued on request. Contact support@s-soundspro.com and we will send the current release for this model.

ARCHITECTURAL & ENGINEERING SPECIFICATION

The LED display system shall be of the Unilumin Upad IV-S type, configured as a tight-curve creative rental LED. The LED display system shall be constructed of 500 × 500 × 80 mm, 7.7 kg. The LED display system shall be covered by the manufacturer's warranty and shall be supplied by Unilumin or a Unilumin-authorized distributor. No alternate shall be accepted without prior written approval of the consultant or specifying engineer.

SAFETY & COMPLIANCE

Read this section before specifying, installing or operating this product. It summarises the safety requirements set out in full in the product documentation supplied with the unit; where the two differ, the product documentation takes precedence.

SUSPENSION & RIGGING

Overhead suspension is potentially hazardous and must be carried out only by trained and competent personnel, using the manufacturer's approved hardware and within the working load limits and configurations published in the manufacturer's own rigging documentation, which takes precedence over anything summarised here. Never exceed the stated number of units per hang. Inspect all rigging components, pins and retaining clips before every deployment and withdraw from service any component that is deformed, corroded or of unknown history. Secondary safety attachment is required where local regulation calls for it.

SOUND PRESSURE LEVEL & HEARING

This equipment is capable of producing sound pressure levels that cause permanent hearing damage. Do not operate at high level in close proximity, and ensure that operators, performers and audience exposure complies with applicable occupational noise-exposure regulation. Provide hearing protection where exposure limits may be exceeded.

ENVIRONMENT & MECHANICAL

Unless a published IP rating states otherwise, this product is intended for indoor use or for outdoor use under cover, and must be protected from rain, standing water and prolonged direct sun. Ensure ventilation openings are unobstructed. Stack, pole-mount and transport only as described in the product documentation, and secure the product against toppling wherever the public has access.

DISPOSAL

At end of life, dispose of the product and any packaging in accordance with local regulation for electrical and electronic equipment. Do not dispose of electronic components in general waste.

WARRANTY

This product is manufactured by Unilumin and carries the manufacturer's own warranty. SSOUNDS supplies it as an authorised distributor and handles warranty claims on your behalf: contact us with proof of purchase and we will obtain a returns reference and manage the process through to resolution. The applicable terms, duration and exclusions are Unilumin's and are issued with the product; we will send you the current version on request. SSOUNDS does not extend its own product warranty to equipment it did not manufacture.

Nothing here affects any statutory rights the purchaser may have under applicable consumer law.

Warranty claims and returns references: support@s-soundspro.com · +44 20 3769 6537

LEGAL NOTICE

All information on this data sheet is published by SSOUNDS as an authorised distributor and is drawn from Unilumin's own published specification. It is subject to change without notice by Unilumin.

Specifications, drawings and images are provided for guidance in system design and tender documentation. Where a figure is critical to a design, confirm it in writing with SSOUNDS before committing to a specification.

Product names, specifications and images are the property of Unilumin. This document, and the SSOUNDS name and marks, are the property of SSOUNDS. All trademarks and registered trademarks are the property of their respective owners.

S SOUNDS PRO LTD

82a James Carter Road, Mildenhall, IP28 7DE, United Kingdom
+44 20 3769 6537 · support@s-soundspro.com

SSOUNDS · ...enhancing listening pleasure! · s-soundspro.com · support@s-soundspro.com
© 2026 S Sounds Pro Ltd. All rights reserved. Specifications subject to change without notice.

SS-DS-UL-UPAD4S-EN-A4 · Rev. 2608 · Issued 14 Aug 2026