

SSOUNDS Wall Mount Bracket

Tilt-adjustable wall and ceiling mount bracket for the M series and M3 column arrays. TÜV certified, rated to 80 kg.



SSOUNDS WALL MOUNT BRACKET

AT A GLANCE

MODEL / SKU	CATEGORY
SS-WMB8	Accessories
BRAND	DRIVE
SSOUNDS	Passive
CONDITION	
New	
APPLICATIONS	
INSTALL	FIXED INSTALLATION
WALL MOUNT	ACCESSORY

OVERVIEW

Steel wall and ceiling mount bracket for the compact SSOUNDS range, TÜV certified and rated to a maximum load of 80 kg. The hinged yoke sets tilt against an angle scale stamped on the bracket itself, from 0 degrees flat to 30 degrees, then locks with captive hardware so the aim cannot drift once the room is tuned. Slotted mounting holes on both plates give lateral adjustment during installation, and the same bracket serves the M-4, M-6 and M-8 point source cabinets and the M3.6P and M3.12P column arrays. Powder-coated steel throughout.

- TÜV certified, rated to a maximum load of 80 kg
- Fits M-4, M-6 and M-8 point source cabinets plus M3.6P and M3.12P column arrays
- Tilt set against an angle scale stamped on the bracket, 0 to 30 degrees
- Captive locking hardware holds the aim after tuning
- Slotted holes on both plates for lateral adjustment during installation
- Wall or ceiling mounting from the same part
- Powder-coated steel

SPECIFICATIONS

GENERAL

Type	Tilt-adjustable wall and ceiling mount bracket
Compatibility	M-4, M-6, M-8, M3.6P, M3.12P
Certifications	TÜV

PHYSICAL & CONSTRUCTION

Material	Powder-coated steel
Mounting	Wall or ceiling
Net weight ¹	7 kg / 15 lb

MECHANICAL

Maximum load	80 kg / 176 lb
Tilt range	0° to 30°, marked scale on the bracket
Adjustment	Slotted mounting holes on both plates
Locking	Captive locking hardware

NOTES

1. Net weight excludes packaging, flight case, accessories and optional rigging hardware.
2. All figures are typical values for production units specified under the conditions above. Individual units may vary within published tolerances.

DOWNLOADS & DATA FILES

SSOUNDS Wall Mount Bracket: User Manual	MANUAL
---	--------

Loudspeaker data files for prediction software (GLL / CLF for EASE), 2D and 3D drawings and certification documents are issued on request. Contact support@s-soundspro.com and we will send the current release for this model.

ARCHITECTURAL & ENGINEERING SPECIFICATION

The unit shall be of the SSOUNDS Wall Mount Bracket type, configured as a tilt-adjustable wall and ceiling mount bracket. The unit shall be constructed of Powder-coated steel, and shall weigh 7 kg / 15 lb. Rigging provision shall be Wall or ceiling. The unit shall be covered by the manufacturer's two (2) year limited warranty and shall be supplied by SSOUNDS or an SSOUNDS-authorized distributor. No alternate shall be accepted without prior written approval of the consultant or specifying engineer.

SAFETY & COMPLIANCE

Read this section before specifying, installing or operating this product. It summarises the safety requirements set out in full in the product documentation supplied with the unit; where the two differ, the product documentation takes precedence.

SUSPENSION & RIGGING

Overhead suspension is potentially hazardous and must be carried out only by trained and competent personnel using SSOUNDS-approved hardware, within the working load limits and array configurations published in the relevant SSOUNDS rigging documentation. Never exceed the stated number of enclosures per array or the stated splay limits. Inspect all rigging components, pins and retaining clips before every deployment and withdraw from service any component that is deformed, corroded or of unknown history. Secondary safety attachment is required where local regulation calls for it. SSOUNDS accepts no liability for systems suspended using non-approved hardware or outside published limits.

SOUND PRESSURE LEVEL & HEARING

This equipment is capable of producing sound pressure levels that cause permanent hearing damage. Do not operate at high level in close proximity, and ensure that operators, performers and audience exposure complies with applicable occupational noise-exposure regulation. Provide hearing protection where exposure limits may be exceeded.

ENVIRONMENT & MECHANICAL

Unless a published IP rating states otherwise, this product is intended for indoor use or for outdoor use under cover, and must be protected from rain, standing water and prolonged direct sun. Ensure ventilation openings are unobstructed. Stack, pole-mount and transport only as described in the product documentation, and secure the product against toppling wherever the public has access.

DISPOSAL

At end of life, dispose of the product and any packaging in accordance with local regulation for electrical and electronic equipment. Do not dispose of electronic components in general waste.

LIMITED WARRANTY: TWO (2) YEARS

SSOUNDS products are warranted against defects in materials and workmanship for a period of two (2) years from the original date of purchase by the end user. Within that period SSOUNDS will, at its option, repair or replace the defective item with no charge for parts or labour. The item must be adequately packaged and dispatched, carriage pre-paid, to SSOUNDS or an SSOUNDS-authorised service centre, accompanied by proof of purchase and a returns reference issued in advance by SSOUNDS. Unauthorised repair, modification or removal of serial-number labelling voids this warranty.

THIS WARRANTY DOES NOT COVER

- Cosmetic wear, finish, grille cloth, paintwork and consumable parts.
- Damage caused by misuse, abuse, accident, neglect, or operation outside the published ratings on this sheet.
- Damage caused by transport or handling after delivery, or by inadequate packaging on return.
- Damage caused by mains or generator supply faults (over-voltage, under-voltage, phase imbalance, surge or incorrect earthing) or by lightning.
- Water, dust or corrosion ingress on products not carrying a published IP rating for the conditions of use.
- Damage resulting from amplification or processing outside the recommended configuration on this sheet, or from third-party presets.
- Products not purchased from SSOUNDS or an SSOUNDS-authorised distributor.

This warranty is in addition to, and does not affect, any statutory rights the purchaser may have under applicable consumer law. It is the sole warranty offered; no other warranty, express or implied, is given.

Warranty claims and returns references: support@s-soundspro.com · +44 20 3769 6537

LEGAL NOTICE

All information on this data sheet is subject to change without notice. SSOUNDS reserves the right to alter specification, design and construction in the course of continuous product development.

Specifications, drawings and images are provided for guidance in system design and tender documentation. Where a figure is critical to a design, confirm it in writing with SSOUNDS before committing to a specification.

All text, images and drawings herein are the property of SSOUNDS. All trademarks and registered trademarks are the property of their respective owners.

S SOUNDS PRO LTD
82a James Carter Road, Mildenhall, IP28 7DE, United Kingdom
+44 20 3769 6537 · support@s-soundspro.com

SSOUNDS · ...enhancing listening pleasure! · s-soundspro.com · support@s-soundspro.com
© 2026 S Sounds Pro Ltd. All rights reserved. Specifications subject to change without notice.

SS-DS-WMB8-EN-A4 · Rev. 2608 · Issued 15 Aug 2026