



SSOUNDS XTO S218

Dual-18" subwoofer module of the XTO System, massive, defined low-end with cardioid-ready configuration for touring and stadiums.

Part of the XTO System. Dual-18 floor subwoofer for large-format and stadium work. XTO stands for Xtended Touring Output. Full system documentation at s-soundspro.com/systems/xto.



SSOUNDS XTO S218 subwoofer, view 2 of 4



SSOUNDS XTO S218 · PRODUCT VIEWS

AT A GLANCE

MODEL / SKU	CATEGORY
SS-XT0-S218	Subwoofers
BRAND	DRIVE
SSOUNDS	Passive
CONDITION	
New	
APPLICATIONS	
TOURING	STADIUM
SUBWOOFER	CARDIOID

OVERVIEW

The XTO S218 is the dual-18" subwoofer module of the XTO System, a bandpass floor design delivering the low-frequency foundation large-format productions demand, reaching all the way to 20 Hz on 5" voice-coil drivers. Deploy in cardioid arrays to keep energy off the stage and out of the back, with the same handle and dolly system as the rest of the system. It is the module that anchors a stadium design under the flagship elements.

- Bandpass dual-18" with 5" voice-coil drivers
- 20 Hz low-frequency reach and 143 dB peak SPL
- Steerable cardioid arrays keep energy off the stage and out of the back
- Fly track and caster dolly shared across the XTO touring inventory
- 18 mm Baltic birch with Polyurea finish
- CardioSteer presets steer low-frequency energy off the stage

TECHNOLOGIES

 DYNACONTROL	Holds the tuned tonal balance as voice coils heat under sustained output.
 CARDIOSTEER	Steerable cardioid arrays that direct low-frequency energy forward.
 FASTSET	Steel and aluminium rigging with captive titanium pins and detented splay for repeatable array geometry.
 SNET	Networked control and monitoring for every amplifier and processor in the system.

SPECIFICATIONS

GENERAL

Type	Bandpass dual-18" touring subwoofer
Certifications	CE · TÜV · EAC · WEEE

ACOUSTIC PERFORMANCE

Frequency response ²	20 Hz - 100 Hz (-10 dB)
Deployment	Omnidirectional · steerable cardioid when arrayed
Sensitivity ³	103 dB SPL nominal (1 W @ 1 m)
Maximum SPL ¹	143 dB peak @ 1 m (half-space)

TRANSDUCERS & COMPONENTS

Low frequency	2 × 18" cone drivers, 5" coil
---------------	-------------------------------

ELECTRICAL

Recommended amplifier power ⁴	4,800 W
Nominal impedance ⁵	4 Ω
Crossover	System low-pass 85 Hz (60 - 100 Hz selectable in the system DSP)

CONNECTORS & I/O

Connectors	2 × NL4 speakON (in / link)
Pin map	1+/1- SUB · 2+/2- not linked

RIGGING & MOUNTING

System	Fly track · caster dolly · cardioid array hardware
--------	--

PHYSICAL & CONSTRUCTION


Dimensions (H × W × D) ⁷	600 × 1200 × 760 mm
Net weight ⁶	117 kg / 258 lb
Enclosure	18 mm Baltic birch · Polyurea finish
Grille	Powder-coated perforated steel with acoustic cloth backing
Handles	2 side · 2 rear recessed
Colour	Black (custom RAL on request)

NOTES

1. Maximum SPL is the peak level at 1 m, driven with pink noise at crest factor 4 to the clipping point of the recommended amplifier, with the SSOUNDS system preset applied. Full-range enclosures are specified under free-field conditions; figures marked half-space are specified over a reflecting plane, the condition subwoofers are deployed in, which adds approximately 6 dB.
2. Frequency response is specified on axis at 1 m in a free field. The tolerance the figure is referenced to is stated alongside it; where no tolerance is given, the figure is the -6 dB bandwidth.
3. Sensitivity is specified at 1 W into the nominal impedance at 1 m on axis, averaged across the pass band of the enclosure.
4. Recommended amplifier power is the amplifier output SSOUNDS specifies for this enclosure, driven with the SSOUNDS system preset. It guides amplifier selection and is not an AES power-handling rating for the transducers.
5. Nominal impedance is the manufacturer's rating for amplifier load calculation; minimum impedance across the operating band may be lower.
6. Net weight excludes packaging, flight case, accessories and optional rigging hardware.
7. Dimensions are stated in millimetres and exclude protruding rigging hardware, handles and connector panels unless noted.
8. All figures are typical values for production units specified under the conditions above. Individual units may vary within published tolerances.

RESPONSE

FREQUENCY RESPONSE




Frequency response: 20 Hz to 100 Hz (-10 dB) · 1/24-octave smoothed


Plot conditions. Curves are generated by the SSOUNDS engineering toolchain from this product's specification. Frequency response is shown 1/24-octave smoothed, normalised to the midband reference, with the passband corners at the stated tolerance; response varies within ± 1 dB across the passband with a subtle shelf in the top octave. Magnitude slopes are 24 dB/octave beyond the passband corners. The beamwidth curve shows the -6 dB included angle: nominal coverage holds down to the pattern-control limit set by the cabinet width ($f \approx c/w$) and widens below it.

DIRECTIVITY

OFF-AXIS ATTENUATION AGAINST FREQUENCY




POLAR RESPONSE, HORIZONTAL



Normalised to on-axis. Rings at 6 dB intervals to a -30 dB centre. 1/3-octave band power.

POLAR RESPONSE, VERTICAL



Normalised to on-axis. Rings at 6 dB intervals to a -30 dB centre. 1/3-octave band power.

Charts span 20 Hz to 100 Hz, this cabinet's own operating band. This cabinet holds within 3 dB of on-axis to 90° right across that band, so an isobar diagram of it would be a single uniform field and is not published. The wavelengths are long against the enclosure, which is why one cabinet radiates as it does; the chart above shows where that begins to change as the top of the passband approaches the baffle width. Pattern control at low frequency comes from how cabinets are arrayed, not from one box. Cardioid, end-fire and gradient arrangements are covered in the engineering notes.

Chart conditions. Directivity charts are computed by the SSOUNDS system prediction engine as a phase-coherent wave solution of this product's driver complement: each way represented by its physical radiator (rigid-piston cones with real diameters and spacings; waveguides as continuous mouth apertures, holding the rated coverage on a flare-controlled axis above the mouth's pattern-control limit and radiating the mouth's own diffraction limit on a wavefront-shaped axis; a horn-loaded mid shares the high-frequency mouth), summed as complex pressure through crossovers at the published points in the topology the cabinet is driven with (linear-phase FIR where the ways run on separate channels of a system DSP amplifier, Linkwitz-Riley where a passive network splits them), with way alignment referenced on axis and 1/24-octave band-power resolution. Single-cabinet vertical figures are free-field beamwidths of one element; the published per-element vertical coverage of a line array is its rigging splay, the sector one element covers in a curved hang. Cabinet edge diffraction, horn loading detail, driver breakup and production tolerances are outside the computation. Directivity files for prediction software (GLL/CLF) are issued from measured data only.

DOWNLOADS & DATA FILES

[SSOUNDS XTO S218: User Manual](#)

MANUAL

[Directivity table, horizontal \(CSV\) / vertical](#)

CSV

Loudspeaker data files for prediction software (GLL / CLF for EASE), 2D and 3D drawings and certification documents are issued on request. Contact support@s-soundspro.com and we will send the current release for this model.

SYSTEM OPERATION

Recommended: SSOUNDS D24X, one channel per XTO S218 (4 Ω) with the S218 preset loaded. Cardioid presets are supplied for three- and four-box arrays.

ARCHITECTURAL & ENGINEERING SPECIFICATION

The subwoofer shall be of the SSOUNDS XTO S218 type, configured as a bandpass dual-18" touring subwoofer. The subwoofer shall incorporate a low-frequency section of 2 x 18" cone drivers, 5" coil. The subwoofer shall be capable of meeting the following performance criteria: a frequency response of 20 Hz – 100 Hz (–10 dB); a maximum sound pressure level of 143 dB peak @ 1 m (half-space); a sensitivity of 103 dB SPL nominal (1 W @ 1 m). Electrically the subwoofer shall provide a nominal impedance of 4 Ω , a crossover at System low-pass 85 Hz (60 – 100 Hz selectable in the system DSP). The unit shall be passive. Connection shall be by 2 x NL4 speakON (in / link). The subwoofer shall be constructed of 18 mm Baltic birch, Polyurea finish, measuring 600 x 1200 x 760 mm, and shall weigh 117 kg / 258 lb. The subwoofer shall be covered by the manufacturer's two (2) year limited warranty and shall be supplied by SSOUNDS or an SSOUNDS-authorized distributor. No alternate shall be accepted without prior written approval of the consultant or specifying engineer.

SAFETY & COMPLIANCE

Read this section before specifying, installing or operating this product. It summarises the safety requirements set out in full in the product documentation supplied with the unit; where the two differ, the product documentation takes precedence.

SUSPENSION & RIGGING

Overhead suspension is potentially hazardous and must be carried out only by trained and competent personnel using SSOUNDS-approved hardware, within the working load limits and array configurations published in the relevant SSOUNDS rigging documentation. Never exceed the stated number of enclosures per array or the stated splay limits. Inspect all rigging components, pins and retaining clips before every deployment and withdraw from service any component that is deformed, corroded or of unknown history. Secondary safety attachment is required where local regulation calls for it. SSOUNDS accepts no liability for systems suspended using non-approved hardware or outside published limits.

SOUND PRESSURE LEVEL & HEARING

This equipment is capable of producing sound pressure levels that cause permanent hearing damage. Do not operate at high level in close proximity, and ensure that operators, performers and audience exposure complies with applicable occupational noise-exposure regulation. Provide hearing protection where exposure limits may be exceeded.

ENVIRONMENT & MECHANICAL

Unless a published IP rating states otherwise, this product is intended for indoor use or for outdoor use under cover, and must be protected from rain, standing water and prolonged direct sun. Ensure ventilation openings are unobstructed. Stack, pole-mount and transport only as described in the product documentation, and secure the product against toppling wherever the public has access.

DISPOSAL

At end of life, dispose of the product and any packaging in accordance with local regulation for electrical and electronic equipment. Do not dispose of electronic components in general waste.

LIMITED WARRANTY: TWO (2) YEARS

SSOUNDS products are warranted against defects in materials and workmanship for a period of two (2) years from the original date of purchase by the end user. Within that period SSOUNDS will, at its option, repair or replace the defective item with no charge for parts or labour. The item must be adequately packaged and dispatched, carriage pre-paid, to SSOUNDS or an SSOUNDS-authorized service centre, accompanied by proof of purchase and a returns reference issued in advance by SSOUNDS. Unauthorised repair, modification or removal of serial-number labelling voids this warranty.

THIS WARRANTY DOES NOT COVER

- Cosmetic wear, finish, grille cloth, paintwork and consumable parts.
- Damage caused by misuse, abuse, accident, neglect, or operation outside the published ratings on this sheet.
- Damage caused by transport or handling after delivery, or by inadequate packaging on return.
- Damage caused by mains or generator supply faults (over-voltage, under-voltage, phase imbalance, surge or incorrect earthing) or by lightning.
- Water, dust or corrosion ingress on products not carrying a published IP rating for the conditions of use.
- Damage resulting from amplification or processing outside the recommended configuration on this sheet, or from third-party presets.
- Products not purchased from SSOUNDS or an SSOUNDS-authorized distributor.

This warranty is in addition to, and does not affect, any statutory rights the purchaser may have under applicable consumer law. It is the sole warranty offered; no other warranty, express or implied, is given.

Warranty claims and returns references: support@s-soundspro.com · +44 20 3769 6537

LEGAL NOTICE

All information on this data sheet is subject to change without notice. SSOUNDS reserves the right to alter specification, design and construction in the course of continuous product development.

Specifications, drawings and images are provided for guidance in system design and tender documentation. Where a figure is critical to a design, confirm it in writing with SSOUNDS before committing to a specification.

All text, images and drawings herein are the property of SSOUNDS. All trademarks and registered trademarks are the property of their respective owners.

S SOUNDS PRO LTD
82a James Carter Road, Mildenhall, IP28 7DE, United Kingdom
+44 20 3769 6537 · support@s-soundspro.com

SSOUNDS · ...enhancing listening pleasure! · s-soundspro.com · support@s-soundspro.com
© 2026 S Sounds Pro Ltd. All rights reserved. Specifications subject to change without notice.
SS-DS-XT0-S218-EN-A4 · Rev. 2608 · Issued 15 Aug 2026